

ZENNA ST RADIAL LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new ST Radial Tire purchased from API bearing the brand name Zenna to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32" as measured in the fastest wearing groove. The life of the original usable tread ends when the tire tread has worn down to 2/32" remaining, at which point the tire is considered to be fully worn out. This warranty applies only to the original purchaser for a period of two (2) years from the date of manufacture. API's liability under this warranty shall be limited to replacement and/or credit for the cost of the tire excluding FET.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Zenna tire becomes unserviceable, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Zenna tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit excluding FET will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining as measured in the fastest wearing groove. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is applicable only in the United States and Canada and any tire used on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 - 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - 2. Tires that are deemed out-of-round or out-of-balance
 - 3. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another;
 - 4. Cost of service, mounting and dismounting.
 - 5. Loss of time or use, inconvenience, or any incidental or consequential damages of any type or nature.

OWNER'S OBLIGATIONS

In order to be eligible for Limited Warranty Service, the owner must:

- A. Present the tire to an authorized dealer;
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer;
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.



ZENNA
High Speed Trailer Tires

ENGINEERED TO PERFECTION

ZENNA RADIAL ST

Tire Size	Load Index (S/D)	Speed Symbol	Ply	Outside Diameter (IN)	Section Width (IN)	Tread Depth (32nds)	Load Capacity (S/D) LBS
ST175/80R13	91/87	N	6	24.0	7.0	7	1360/1200
ST205/75R14	105/101	N	8	26.1	8.0	7	2040/1820
ST215/75R14	102/98	N	6	26.7	8.5	7	1870/1650
ST205/75R15	107/102	N	8	27.1	8.0	8	2150/1870
ST225/75R15	117/112	N	10	28.3	8.8	8	2830/2470
ST225/90R16	122/118	N	14	31.8	8.7	8	3300/2910
ST235/80R16	126/122	N	12	30.8	9.3	8	3640/3200
ST235/85R16	129/125	N	14	31.7	9.3	8	4080/3640
ST235/85R16	132/127	N	14	31.7	9.3	8	4400/3860



- Specialty trailer tire designed for recreational vehicles and light industrial use
- Advanced tread compound designed to improve fuel economy and resist weather cracking
- Designed with stone ejectors between the tread area to protect casing and prevent stone drilling tread life
- High speed (N) rating

ZENNA ALL STEEL RADIAL

Tire Size	Load Index (S/D)	Speed Symbol	Ply	Outside Diameter (IN)	Section Width (IN)	Tread Depth (32nds)	Load Capacity (S/D) LBS
ST235/80R16	128/124	N	14	30.8	9.3	10.5	3960/3520
ST235/85R16	129/125	N	14	31.7	9.3	10.5	4080/3640
ST235/85R16	132/127	N	14	31.7	9.3	10.5	4400/3860



- High mileage ST designed for continuous use
- Ideal for heavy industrial and hauling equipment
- All steel construction for added strength and stability
- Designed with stone ejectors between the tread area to protect casing and prevent stone drilling tread life
- High speed (N) rating

PERFORMANCE GUARANTEED®