

ZENNA[®]

High Speed Trailer Tires

ZENNA ST RADIAL LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new ST Trailer Tire purchased from API bearing the brand name Zenna to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32" as measured in the fastest wearing groove. The life of the original usable tread ends when the tire tread has worn down to 2/32" remaining, at which point the tire is considered to be fully worn out. This warranty applies only to the original purchaser for a period of two (2) years from the date of manufacture. API's liability under this warranty shall be limited to replacement and/or credit for the cost of the tire excluding FET.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Zenna tire becomes unserviceable, API will do either of the following:

- A) If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Zenna tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B) If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit excluding FET will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining as measured in the fastest wearing groove. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

Adjustment credit for out-of-balance or out-of-round tires is not covered by this warranty

EXCLUSIONS

- A) All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B) This limited warranty is applicable only in the United States, Canada or Mexico and any tire used on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C) The following is not covered by the Limited Warranty:
 - 1) Tires branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - 2) Tires that are deemed out-of-round or out-of-balance
 - 3) Failure, damage or irregular wear due to:
 - a) Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b) Fire, accident or vandalism;
 - c) Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d) Misapplication of the tire, use of improper inner tube;
 - e) Alteration of the tire or addition of foreign material or transfer from one vehicle to another;
 - 4) Cost of service, mounting and dismounting.
 - 5) Loss of time or use, inconvenience, or any incidental or consequential damages of any type or nature.

OWNER'S OBLIGATIONS

In order to be eligible for Limited Warranty Service, the owner must:

- A) Present the tire to an authorized dealer;
- B) Present proof of purchase to the satisfaction of the dealer;
- C) Complete and sign an API Warranty Claim Form, which is available from any authorized dealer; and
- D) Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

EXPERIENCE / THE DIFFERENCE[®]



ZENNA[®]

High Speed Trailer Tires



ZENNA ST OCT 2018 - US, CAN & MEX

RADIAL ST

| TIRE SIZE | TIRE PLY | LOAD INDEX (S/D) | SPEED SYMBOL | OVERALL DIAMETER (INCHES) | SECTION WIDTH (INCHES) | TREAD DEPTH (32nds) | MAXIMUM LOAD CAPACITY (S/D, LBS) |
|-------------|----------|------------------|--------------|---------------------------|------------------------|---------------------|----------------------------------|
| ST175/80R13 | 6 | 91/87 | N | 24.0 | 7.0 | 9 | 1360/1200 |
| ST205/75R14 | 6 | 100/96 | N | 26.1 | 8.0 | 9 | 1760/1570 |
| ST215/75R14 | 6 | 102/98 | N | 26.7 | 8.5 | 9 | 1870/1650 |
| ST205/75R15 | 6 | 101/97 | N | 27.1 | 8.0 | 9 | 1820/1610 |
| ST205/75R15 | 8 | 107/102 | N | 27.1 | 8.0 | 9 | 2150/1870 |
| ST225/75R15 | 8 | 113/108 | N | 28.3 | 9.2 | 9 | 2540/2200 |
| ST225/75R15 | 10 | 117/112 | N | 28.3 | 9.2 | 9 | 2830/2470 |
| ST225/90R16 | 14 | 122/118 | N | 31.8 | 8.7 | 10 | 3300/2910 |
| ST235/80R16 | 10 | 124/120 | N | 30.8 | 9.3 | 10 | 3520/3080 |
| ST235/85R16 | 12 | 128/124 | N | 31.7 | 9.3 | 10 | 3960/3520 |
| ST235/85R16 | 14 | 129/125 | N | 31.7 | 9.3 | 10 | 4080/3640 |



Specialty trailer tire designed for recreational vehicle and light industrial use

Advanced tread compound designed to improve fuel economy and resist weather cracking

Designed with stone ejectors between the tread area to protect casing and prevent stone drilling tread life

High speed (N) Rating

ALL STEEL RADIAL

| TIRE SIZE | TIRE PLY | LOAD INDEX (S/D) | SPEED SYMBOL | OVERALL DIAMETER (INCHES) | SECTION WIDTH (INCHES) | TREAD DEPTH (32nds) | MAXIMUM LOAD CAPACITY (S/D, LBS) |
|-------------|----------|------------------|--------------|---------------------------|------------------------|---------------------|----------------------------------|
| ST235/80R16 | 14 | 128/124 | N | 30.8 | 9.3 | 10 | 3960/3520 |
| ST235/85R16 | 14 | 129/125 | N | 31.7 | 9.3 | 10 | 4080/3640 |



High mileage ST designed for continuous use

Ideal for heavy industrial and hauling equipment

All steel construction for added strength and stability

Designed with stone ejectors between the tread area to protect casing and prevent stone drilling tread life

High speed (N) Rating

QUALITY SPEAKS FOR ITSELF®

EXPERIENCE THE DIFFERENCE®