

ZENNA[®]

Commercial Truck Tires

STANDARD LIMITED WARRANTY

API hereby warrants every new Zenna Commercial Truck tire for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tread has worn to 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be worn out. API will credit the purchaser a prorated amount based on the usable tread remaining excluding FET. All Exclusions listed below void this Standard Limited Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) Submission of claims covered by this warranty constitutes adherence to the terms of this warranty as detailed herein.
- B) This warranty applies only to new first quality tires. Blemished tires and road hazard damaged tires are specifically excluded.
- C) Tires returned for ride complaints, balance issues or out of round are excluded from this warranty if they are worn past 2/32" from the original tread of the new tire.

CASING WARRANTY

- A) Casings of Zenna Commercial Truck tires are warranted for workmanship and material related conditions through the life of the first retread or 5 years from the date of manufacture, whichever comes first.
- B) If an examination shows that a casing of a Zenna Commercial Truck tire was deemed not retreadable due to a workmanship or material related condition, API will give credit as follows:

All 17.5 inch rim sizes: \$15.00	11R22.5, 12R22.5, 295/75R22.5, 295/80R22.5: \$50.00
All 19.5 inch rim sizes: \$25.00	11R24.5, 285/75R24.5: \$50.00
255/70R22.5, 275/70R22.5: \$40.00	

EXCLUSIONS

The following is NOT covered by the Zenna Commercial Truck Standard Limited Warranty:

- 1) Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
- 2) Failure, damage or irregular wear due to:
 - a) road hazards (i.e. puncture, cut, snag, impact breaks, etc.), wreck, collision;
 - b) fire, accident or vandalism;
 - c) mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d) overloading the tire beyond maximum load capacity stated on the sidewall;
 - e) misapplication of tire, use of improper inner tube/ flap;
 - f) alteration of the tire or addition of foreign material.
 - g) transfer from one vehicle to another and tire failure due to faulty retread process or materials.

OWNER'S OBLIGATIONS

In order to be eligible for Zenna Commercial Truck Warranty service, the owner must:

- A) present the tire to an authorized dealer from which the original purchase was made;
- B) present proof of purchase to the satisfaction of the dealer;
- C) complete and sign an API Warranty Claim Form, which is available at any authorized dealer; and
- D) pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Zenna Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

EXPERIENCE
THE DIFFERENCE[®]



ZENNA[®]

Commercial Truck Tires



ENGINEERED TO PERFECTION[®]



AP-250

- All position tire best suited for steer axle applications
- Steel belted for toughness, stability and uniform wear

TIRE SIZE	TIRE PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OVERALL DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32nds)	MAXIMUM LOAD CAPACITY (S/D LBS)
215/75R17.5	16	135/133	J	30.2	8.4	16	4805/4540
225/70R19.5	14	128/126	M	31.9	8.9	16	3970/3750
235/75R17.5	16	143/141	J	31.4	9.2	16	6005/5675
245/70R19.5	16	135/133	M	33	9.8	16	4805/4540
255/70R22.5	16	140/137	M	36.6	10	15	5510/5070
295/75R22.5	14	144/141	L	39.9	11.7	18	6175/5675
11R22.5	14	144/142	M	41.5	11	18	6175/5840
11R22.5	16	146/143	M	41.5	11	18	6610/6005
11R24.5	14	146/143	L	43.5	11	18	6610/6005
11R24.5	16	149/146	L	43.5	11	18	7160/6610



DR-850

- Deep tread, closed shoulder drive tire designed for long haul and even wear
- Steel belt package designed for outstanding wear in long haul applications

TIRE SIZE	TIRE PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OVERALL DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32nds)	MAXIMUM LOAD CAPACITY (S/D LBS)
295/75R22.5	14	144/141	L	40.4	11.7	27	6175/5675
11R22.5	14	144/142	M	41.9	11	27	6175/5840
11R22.5	16	146/143	M	41.9	11	27	6610/6005
11R24.5	14	146/143	L	43.9	11	27	6610/6005
11R24.5	16	149/146	L	43.9	11	27	7160/6610

QUALITY SPEAKS FOR ITSELF®



MP-860

- Mixed service tire with cut and chip resistant tread compound for on/off road applications
- Steel belted for tread stability and casing durability

TIRE SIZE	TIRE PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OVERALL DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32nds)	MAXIMUM LOAD CAPACITY (S/D LBS)
255/70R22.5	16	140/137	N	36.6	10	18	5510/5070
11R22.5	16	146/143	N	41.7	11	19	6610/6005
11R24.5	16	149/146	N	43.7	11	20	7160/6610



TR-100

- All position tire designed specifically for trailer applications
- Steel belted for toughness, stability and uniform wear

TIRE SIZE	TIRE PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OVERALL DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32nds)	MAXIMUM LOAD CAPACITY (S/D LBS)
295/75R22.5	14	144/141	L	39.9	11.7	12	6175/5675
11R22.5	14	144/142	M	41.5	11	12	6175/5840
11R22.5	16	146/143	M	41.5	11	12	6610/6005
11R24.5	14	146/143	L	43.5	11	12	6610/6005
11R24.5	16	149/146	L	43.5	11	12	7160/6610

EXPERIENCE THE DIFFERENCE®