

Gladiator®

Steel-Belted Radial Commercial Truck Tires



**FUEL
EFFICIENT**



**RETREADABLE
CASING**



**BUILT TO
PERFORM**



**INDUSTRY
LEADING
WARRANTY**

EXPERIENCE THE DIFFERENCE®

TIRES DESIGNED FOR TODAY'S FLEETS AND TOMORROW'S DEMANDS.

Gladiator[®]

Steel-Belted Radial Commercial Truck Tires



***BUILT FOR TODAY'S FLEETS.
ENGINEERED FOR TOMORROW'S ROADS.***

Gladiator Steel-Belted Radial Commercial Truck Tires are engineered with advanced technology and premium materials to deliver exceptional performance, mile after mile.



FUEL EFFICIENT

Low rolling resistance compounds help reduce fuel consumption.



RETREADABLE CASING

Built with durability in mind for multiple retread cycles.



FLEET PERFORMANCE

Engineered for stability, handling and long, uniform treadwear.



INDUSTRY-LEADING WARRANTY

Backed by one of the most comprehensive warranties in the industry.

ENGINEERED TO PERFECTION[®]

FEATURES AND BENEFITS:

GLADIATOR G-SERIES

The Gladiator G Series Commercial Truck Tire product line offers a comprehensive range of tire solutions designed to meet the demands of nearly every commercial trucking application. Whether your fleet operates on long interstate routes, regional delivery networks, urban streets, construction sites, or in changing weather conditions, Gladiator G-Series has a tire engineered to deliver dependable performance, durability, and value.

ENGINEERED TO PERFECTION®

- **GLADIATOR CASINGS** utilize a cap base construction and are tested well beyond the regulatory requirements resulting in an enhanced warranty of 7 years and 3 retreads.
- **GLADIATOR TREAD COMPOUNDS** are formulated with the latest technological advances to ensure maximum performance and durability for every application.
- **GLADIATOR ADVANCEMENTS** in structural integrity of the tread surface result in less tread squirm, greater stability and long-lasting performance.
- **GLADIATOR TECHNOLOGY** utilizes a two compound filler in the bead contour which facilitates a more exact, concentric fitment in the mounting process. This promotes greater overall uniformity and eliminates vibration regardless of the application.
- **GLADIATOR MANUFACTURING PROCESS** requires that every tire be balanced and uniformity-tested prior to release facilitating a 100% replacement guarantee for defects down to 2/32nds. This promotes confidence in placing the Gladiator Truck Tire in any application.

INDUSTRY LEADING WARRANTY COVERAGE

Supporting the Gladiator G-Series is a comprehensive warranty program designed to provide fleets and owner-operators with confidence long after the sale. Gladiator Commercial Truck Tires are backed tire and casing warranty protection that reflects our commitment to quality, durability, and long-term value.

From our 100% Free Replacement Warranty to our 7-Year, 3-Retread Casing Warranty, American Pacific Industries, Inc. stands behind every tire with coverage designed to maximize tire life, protect your investment, and keep your operation moving. (See Warranty page for details). No matter the application—Line Haul, Regional, Urban, On/Off Highway, or All-Weather—Gladiator delivers the performance you need and the warranty support you can trust.



GLADIATOR ADVANTAGE:



PREMIUM MATERIALS

Quality compounds and construction for long tread life.



RETREADABLE CASING

Built for multiple retreads to lower cost per mile.



COST-EFFICIENT

Lower rolling resistance to reduce fuel costs.



LEADING WARRANTY

Backed by one of the most comprehensive warranties in the industry.

ENGINEERED TO PERFECTION®

Gladiator tires are built with advanced engineering and premium materials to deliver enhanced performance, long tread life and total cost savings for your fleet.



UNIFORM WEAR

Optimized footprint and tread design deliver even wear and maximum mileage.



RETREAD CAPABILITY

Rugged casing design supports multiple retreads, lowering you cost per mile.



SUPERIOR HEAT DISSIPATION

Advanced casing construction promotes cooler running for longer tire life.



FACTORY BALANCED

Every tire is factory balanced and tested for free radial runout to ensure a smooth, comfortable ride.

GLADIATOR G LINE -

PAGE 5:

G550-AP

All-Position Steer

G400-AP

All-Position

PAGE 6:

G350-TR

Shallow Tread Trailer

G900-PED

Premium Closed Shoulder Drive

PAGE 7:

G990-PD

Closed Shoulder Drive

G920-POS

Premium Open Shoulder Drive

PAGE 8:

G770-DL

Open Shoulder Drive

G750-OSD

Regional / Urban OSD Drive

PAGE 9:

G780-AWS

All-Weather Regional/Urban OSD Drive

G880-MS

Premium Mixed-Service All-Position

G860-MP

Mixed-Service All-Position

PAGE 10:

QR84-PED

On / Off Highway Drive

G880-HD

Severe Service Drive



G550-AP



ALL-POSITION STEER / LINE HAUL & REGIONAL

- Designed for steer axles and all-position usage with sidewall grooves to improve resistance to irregular wear
- Advanced casing construction delivers the strength and reliability required for demanding commercial applications.
- Wider tread for superior tread life, greater traction and improved retreadability.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.5	11.0	18	6175/5840
11R22.5/16	146/143	M	41.5	11.0	18	6610/6005
11R22.5/16	148/145	M	41.5	11.0	18	6940/6395
11R22.5/18	149/146	M	41.5	11.0	18	7160/6610
11R24.5/14	146/143	L	43.5	11.0	18	6610/6005
11R24.5/16	149/146	L	43.5	11.0	18	7160/6610
11R24.5/18	152/149	L	43.5	11.0	18	7830/7160
285/75R24.5/14	144/141	L	41.3	11.1	18	6175/5675
285/75R24.5/16	147/144	L	41.3	11.1	18	6780/6175
295/75R22.5/14	144/141	L	39.9	11.7	18	6175/5675
295/75R22.5/16	146/143	L	39.9	11.7	18	6610/6005
295/75R22.5/18	148/145	L	39.9	11.7	18	6940/6395



G400-AP



ALL-POSITION / REGIONAL & URBAN

- All-position tire for regional and metro applications
- Wide 5-rib tread design and tread siping features resist irregular tread wear.
- Optimized shoulder profile and shoulder wall grooves help deliver excellent uneven rib wear.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
215/75R17.5/16	135/133	L	30.2	8.4	15	4805/4540
225/70R19.5/12	125/123	N	31.9	9.0	15	3640/3415
225/70R19.5/14	128/126	N	31.9	9.0	15	3970/3750
235/75R17.5/16	143/141	L	31.4	9.2	15	6005/5675
235/75R17.5/18	143/141	L	31.4	9.2	15	6005/5675
245/70R17.5/18	143/141	L	31.1	9.8	15	6005/5675
245/70R19.5/16	135/133	N	33.0	9.8	15	4805/4540
255/70R22.5/16	140/137	M	36.6	10.0	14	5510/5070
265/70R19.5/18	143/141	J	34.1	10.3	17	6005/5675
275/70R22.5/18	148/145	M	37.7	10.9	17	6940/6395
315/80R22.5/20	157/154	L	42.4	12.3	18	9090/8270
315/80R22.5/20	161/154	L	42.4	12.3	18	10200/8270



G350-TR



SHALLOW TREAD TRAILER

- Shallow tread highway tire designed to reduce irregular wear in trailer position.
- Optimized casing construction promotes even footprint pressure and long, predictable treadwear.
- New tread design distributes load evenly across the footprint for smooth, uniform wear and increased tread life.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.5	11.0	11	6175/5840
11R22.5/16	146/143	M	41.5	11.0	11	6610/6005
11R22.5/16	148/145	M	41.5	11.0	11	6940/6395
11R24.5/14	146/143	L	43.5	11.0	11	6610/6005
11R24.5/16	149/146	L	43.5	11.0	11	7160/6610
285/75R24.5/14	144/141	L	41.3	11.1	11	6175/5675
285/75R24.5/16	147/144	L	41.3	11.1	11	6780/6175
295/75R22.5/14	144/141	L	39.9	11.7	11	6175/5675
295/75R22.5/16	146/143	L	39.9	11.7	11	6610/6005



G900-PED



PREMIUM CLOSED SHOULDER DRIVE

- Deep closed shoulder design provides traction and long-lasting tread life for demanding drive-axle applications.
- Enhanced casing construction withstands the demands of drive-axle service while supporting long-term durability.
- Large lugs distribute load evenly across the footprint for smooth, uniform wear and increased tread life.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.9	11.0	29	6175/5840
11R22.5/16	146/143	M	41.9	11.0	29	6610/6005
11R22.5/16	148/145	M	41.9	11.0	29	6940/6395
11R24.5/14	146/143	L	43.9	11.0	29	6610/6005
11R24.5/16	149/146	L	43.9	11.0	29	7160/6610
295/75R22.5/14	144/141	L	40.4	11.7	29	6175/5675
295/75R22.5/16	146/143	L	40.4	11.7	29	6610/6005



G990-PD



CLOSED SHOULDER DRIVE

- Aggressive closed shoulder design with zig-zag grooves create additional biting edges for improved traction and grip.
- Next-generation casing design built to maximize tire performance throughout multiple life cycles.
- A wider tread face distributes load evenly across the contact patch, promoting long, even wear and improved mileage.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.9	11.0	28	6175/5840
11R22.5/16	146/143	M	41.9	11.0	28	6610/6005
11R22.5/16	148/145	M	41.9	11.0	28	6940/6395
11R22.5/18	149/146	M	41.9	11.0	28	7160/6610
11R24.5/14	146/143	L	43.9	11.0	28	6610/6005
11R24.5/16	149/146	L	43.9	11.0	28	7160/6610
11R24.5/18	152/149	L	43.9	11.0	28	7830/7160
285/75R24.5/14	144/141	L	41.8	11.1	28	6175/5675
285/75R24.5/16	147/144	L	41.8	11.1	28	6780/6175
295/75R22.5/14	144/141	L	40.4	11.7	28	6175/5675
295/75R22.5/16	146/143	L	40.4	11.7	28	6610/6005
295/75R22.5/18	148/145	L	40.4	11.7	28	6940/6395



G920-POS



PREMIUM OPEN SHOULDER DRIVE

- Deep closed shoulder design provides traction and long-lasting tread life for demanding drive-axle applications.
- Enhanced casing construction withstands the demands of drive-axle service while supporting long-term durability.
- Large lugs distribute load evenly across the footprint for smooth, uniform wear and increased tread life.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.9	11.0	28	6175/5840
11R22.5/16	146/143	M	41.9	11.0	28	6610/6005
11R22.5/16	148/145	M	41.9	11.0	28	6940/6395
11R24.5/14	146/143	L	43.9	11.0	28	6610/6005
11R24.5/16	149/146	L	43.9	11.0	28	7160/6610



G770-DL



OPEN SHOULDER DRIVE

- Open-shoulder design with aggressive blocks and multiple biting edges provide superior traction and grip.
- Advanced casing and updated tread design engineered for improved strength and durability.
- Integrated tie bars improve stability while reducing irregular tread wear.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.9	11.0	25	6175/5840
11R22.5/16	146/143	M	41.9	11.0	25	6610/6005
11R22.5/16	148/145	M	41.9	11.0	25	6940/6395
11R24.5/14	146/143	L	43.9	11.0	25	6610/6005
11R24.5/16	149/146	L	43.9	11.0	25	7160/6610

G750-OSD



REGIONAL / URBAN OSD DRIVE

- Open-shoulder drive tread pattern for excellent traction and long treadlife.
- Staggered tread block design distributes forces evenly to help resist irregular wear for longer tire life.
- Strategically designed tread blocks with multiple biting edges provide outstanding traction and enhanced grip.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
225/70R19.5/12	125/123	N	32.2	8.9	18	3640/3415
225/70R19.5/14	128/126	N	32.2	8.9	18	3970/3750
245/70R19.5/16	135/133	N	33.3	9.8	18	4805/4540



G780-AWS



ALL-WEATHER REGIONAL / URBAN OSD DRIVE

- Open shoulder tread pattern cleans out well in snow and mud conditions for excellent all-weather performance.
- Extensive sipes in tread pattern for exceptional tire traction in both ice and snow.
- 3-peak mountain snowflake certified with ability to accept TSMI #15 winter studs for use in extreme winter conditions.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
225/70R19.5/14	128/126	N	32.2	8.9	17	3970/3750
225/70R19.5/16	130/128	N	32.2	8.9	17	4190/3970



G880-MS



PREMIUM MIXED-SERVICE / ALL-POSITION

- Enhanced casing construction to withstand the demands of on/off road applications supporting long-term durability.
- Application specific tread compounds resist tread chipping in high-scut applications.
- Stone defense features in the base of the tread groove promote casing integrity.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.7	11.0	21	6175/5840
11R22.5/16	146/143	M	41.7	11.0	21	6610/6005
11R22.5/16	148/145	M	41.7	11.0	21	6940/6395
11R24.5/14	146/143	L	43.7	11.0	21	6610/6005
11R24.5/16	149/146	L	43.7	11.0	21	7160/6610
385/65R22.5/20	160	K	42.4	15.3	21	9920



G860-MP



MULTI-SERVICE / ALL-POSITION

- All-position tread pattern designed for multiple on/off highway applications.
- Application specific tread compounds resist tread chipping in high-scut on and off-road applications.
- Outside shoulder grooves with zigzag center grooves provide added traction in mud and soft soil.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	N	41.7	11.0	18	6175/5840
11R22.5/16	146/143	N	41.7	11.0	18	6610/6005
11R22.5/16	148/145	N	41.7	11.0	18	6940/6395
11R24.5/14	146/143	N	43.7	11.0	19	6610/6005
11R24.5/16	149/146	N	43.7	11.0	19	7160/6610
255/70R22.5/16	140/137	N	36.9	10.0	17	5510/5070
315/80R22.5/20	161/154	K	42.6	12.3	21	10200/8270



QR84PED



ON / OFF HIGHWAY DRIVE

- Extra deep 32/32nds drive tire for long life even in challenging off-road applications.
- Specialized tread compounds and stone defense groove design resist chipping, cuts, casing damage for longer tire life.
- Enhanced tread voids provide outstanding traction in loose dirt, sand, snow, and demanding logging environments.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R22.5/14	144/142	M	41.9	11.0	31	6175/5840
11R22.5/16	146/143	M	41.9	11.0	31	6610/6005
11R22.5/16	148/145	M	41.9	11.0	31	6940/6395
11R24.5/14	146/143	L	43.9	11.0	31	6610/6005
11R24.5/16	149/146	L	43.9	11.0	31	7160/6610



G880-MS



SEVERE SERVICE DRIVE

- Aggressive multi-lug drive tire design for traction in severe off-highway operations.
- Extra deep 29/32nds tire for long life even in challenging off-road applications.
- Application-specific tread compound resists cutting and chipping promoting increased mileage and long service life.

TIRE SIZE/PLY	LOAD INDEX (S/D)	SPEED SYMBOL	OUTSIDE DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32nds)	LOAD CAPACITY LBS (S/D)
11R24.5/16	149/146	L	44.0	11.0	29	7160/6610

GLADIATOR G-SERIES RADIAL COMMERCIAL TRUCK TIRE WARRANTY

100% FREE REPLACEMENT WARRANTY

American Pacific Industries, Inc. (API) hereby warrants every new Gladiator G-Series Radial Commercial Truck Tire for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has worn to 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out. API will refund the cost of a replacement Gladiator G-Series Commercial Truck tire excluding FET. All Exclusions listed below void this 100% Free Replacement Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) The Gladiator G-Series Commercial Truck tire must be replaced with a comparable new Gladiator G-Series Commercial Truck Commercial Truck tire by an authorized Gladiator dealer. Copy of the invoice may be required.
- B) Submission of claims covered by this warranty constitutes adherence to the terms of this warranty as detailed herein.
- C) Cost of mounting and balancing will be refunded up to a maximum of \$16.00 per tire. Written proof of these costs will be required.
- D) 100% free replacement applies to new first quality tires only. Blemished tires, retreads and road hazard tires are specifically excluded.
- E) Adjustments for ride complaints, out of balance or out of round tires are excluded from this warranty if they are worn past 2/32" from the original usable tread of the new tire as measured in the fastest wearing groove.

CASING WARRANTY

- A) Casings of Gladiator G-Series Commercial Truck Tires are warranted for workmanship and material related conditions through the life of the third retread or 7 years from date of manufacturer, whichever comes first. The life of the third retread is considered to end when the remaining tread on the third retread reaches a buffing stage of 2/32" or less as measured in the fastest wearing groove.
- B) If an examination shows that a casing of a Gladiator G-Series Commercial Truck Tire was removed from service due to workmanship or a material related condition, API will give a credit toward the purchase of a new Gladiator G-Series Commercial Truck Tire as below:

Above casing warranty valid only for first seven (7) years after date of manufacture of original tire.

<i>Eligible Sizes</i>	<i>1st to 2nd Retread</i>	<i>3rd Retread</i>
17.5"	\$30.00	\$15.00
19.5"	\$30.00	\$15.00
255/70R22.5, 275/70R22.5	\$65.00	\$35.00
11R22.5, 295/75R22.5	\$90.00	\$45.00
315/80R22.5	\$85.00	\$40.00
11R24.5, 285/75R24.5	\$90.00	\$45.00
385/65R22.5	\$85.00	\$40.00

EXCLUSIONS

- A) All Gladiator G-Series Commercial Truck Tire warranties are limited to the original purchaser and the original vehicle on which they are mounted for a period of seven (7) years from the date of manufacture and are not assignable to subsequent purchasers or vehicles.
- B) The Gladiator G-Series Commercial Truck Tire warranties are applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by this warranty.
- C) The following is not covered by the Gladiator G-Series Commercial Truck Tire Warranty:
 - 1) Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - 2) Failure, damage or irregular wear due to:
 - a) Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b) Fire, accident or vandalism;
 - c) Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d) Overloading the tire beyond maximum load capacity stated on the sidewall;
 - e) Misapplication of tire, use of improper inner tube/ flap;
 - f) Alteration of the tire or addition of foreign material.
 - g) Transfer from one vehicle to another and tire failure due to faulty retread process or materials.
 - 3) Cost of mounting and balancing service except as noted above.
 - 4) Loss of time or use, inconvenience, or any incidental damages to include cost of towing or transportation, related property damage or consequential damages of any type or nature except as prohibited by law.
 - 5) Tires older than seven (7) years from the date of manufacture as determined by the DOT/Serial number.
 - 6) Tires with an ST designation that are deemed out-of-round or out-of-balance

OWNER'S OBLIGATIONS

In order to be eligible for Gladiator G-Series Commercial Truck Tire Warranty service, the owner must:

- A) Present the tire to an authorized dealer;
- B) Present proof of purchase to the satisfaction of the dealer;
- C) Complete and sign an API Warranty Claim Form, which is available at any authorized dealer; and
- D) Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Gladiator G-Series Commercial Truck Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

Gladiator[®]

Steel-Belted Radial Commercial Truck Tires



800.944.8414



GLADIATORTIRES.COM