

EXPERIENCE THE DIFFERENCE®

Gladiator® Tires



ON AND OFF HIGHWAY TIRES

BIAS LT | BIAS TRUCK | BIAS TRAILER

AGRICULTURAL | INDUSTRIAL | OFF THE ROAD | SPECIALTY

Gladiator[®]

Tires

ON AND OFF HIGHWAY TIRE INDEX

ON HIGHWAY 4

BIAS TRUCK

HIGHWAY	4
CROSSBAR	4
TRAILER LPT	5

BIAS LIGHT TRUCK

LT HIGHWAY	5
LT TRACTION	6

TRAILER

LOW BOY	6
QR-15-STB	7
HST	7

AGRICULTURAL 8

REAR FARM R1

TRACTOR R1	8
------------	---

REAR FARM G-1

TRACTOR R1/G1	9
---------------	---

IRRIGATION

PIVOT WORKS R1	9
PIVOT WORKS ND	10

REAR FARM R-4

INDUSTRIAL R4	10
---------------	----

TRACTION IMPLEMENT I-3/R-4

TRACTION I-3	11
--------------	----

FRONT FARM

FRONT FARM 4R F-2M	11
FRONT FARM F-2	12
INDUSTRIAL FRONT F-3	12

IMPLEMENT

IMPLEMENT I-1	13
HIGHWAY SERVICE FI	13

ON AND OFF HIGHWAY TIRE INDEX CONTINUED

INDUSTRIAL AND OTR 14

SKID STEER

SKS RG	14
SKS RD HD	14
SKS TRAX ND	15
SKS L-4 HD	15

TRENCHER

TRENCHER	15
----------	----

FORKLIFT

POWER LIFT HD	16
---------------	----

OFF-THE-ROAD

GRADER G-2	17
LOADER L-2	17

SPECIALTY 18

SPECIALTY AG/TRENCHER

AG TRAC	18
---------	----

GOLF CART

PRO	18
P4C	18
PGC	19

LAWN & GARDEN

TURF	19
S-TURF	20
STRAIGHT RIB	20
TURF TRAC	21
SMOOTH	21
SAWTOOTH	21
STUD	22
WHEELBARROW	22

ATV/SXS

KNOBBY	23
MUD & SNOW	23
TRAIL HD	23
R/T UTV	24
XTR UTV RADIAL	25

WARRANTY 26

BIAS TRUCK**Gladiator HIGHWAY**

An All-Position tire designed for use on trucks and trailers in commercial applications

- Rib tread pattern – Straight ribs for good directional stability and even wear
- High load-carrying capacity – Suitable for heavy trucks and commercial use
- Strong sidewall durability – Resists cuts, impacts, and rough road damage



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164087502	7.50-20	125/121G	E/10	TT+FLAP	6.0	8	37	18	3640
1164088252	8.25-20	136/132L	G/14	TT+FLAP	6.5	9	38	22	4940
1164089002	9.00-20	141/137L	G/14	TT+FLAP	7.0	10	40	21	5675
1164081002	10.00-20	146/142L	H/16	TT+FLAP	7.5	11	42	22	6610

* TT + FLAP = TUBETYPE TIRE WITH FLAP

BIAS TRUCK**Gladiator CROSSBAR**

Suitable for drive & steer positions – especially effective on multi-wheel drive trucks

- Crossbar tread design – Deep, transverse lugs for excellent traction
- High tractive performance – Strong grip on loose, muddy, sandy, and rough roads
- Strong carcass construction – Handles heavy loads and torque



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164078252	8.25-20 WF	136/132L	G/14	TT+FLAP	6.5	9	39	23	4940
1164079002	9.00-20	141/137L	G/14	TT+FLAP	7.0	10	40	25	5675
1164071002	10.00-20	146/142L	H/16	TT+FLAP	7.5	11	42	23	6610

* TT + FLAP = TUBETYPE TIRE WITH FLAP

BIAS TRUCK**Gladiator TRAILER LPT**

Designed for low platform or drop-deck trailers

- High load-carrying capacity – engineered for concentrated trailer axle loads
- Wide tread footprint – improves stability and even load distribution
- Durable carcass construction withstands high stress and long haulage



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164107515	7.50-15TR	124/120L	G/14	TT+FLAP	6.0	9	32	19	3525
1164108251	8.25-15TR	132/127L	H/16	TT+FLAP	6.5	9	33	18	4410
1164109015	9.00-15TR	135/130L	G/14	TT+FLAP	7.0	10	35	21	4805
1164101015	10.00-15TR	141/136L	H/16	TT+FLAP	7.5	11	37	25	5675

* TT + FLAP = TUBETYPE TIRE WITH FLAP

BIAS LIGHT TRUCK**Gladiator LT HIGHWAY**

All-Position tire for powered vehicles or trailers

- Long-wearing, all-position premium rib tire
- Bias ply construction with diagonally laid nylon plies for strength
- Strong, stiff sidewalls for stability under load



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164115702	7.00-15	105/101L	D/8	TL	5.5	8	30	14	2040
1164116753	7.50-16	116/112L	E/10	TL	6.0	9	32	14	2775
1164116803	8.00-16.5	110/105J	E/10	TL	6.0	8	28	17	2335
1164116873	8.75-16.5	115/111J	E/10	TL	6.8	9	29	17	2680
1164116953	9.50-16.5	121/117J	E/10	TL	6.8	10	31	17	3195
1164116124	12-16.5LT	129/125L	F/12	TL	9.8	12	32	22	4080

BIAS LIGHT TRUCK**Gladiator LT TRACTION**

Traction tire for specialized applications and off-road use

- Aggressive tread for traction in on or off-road usage
- Bias ply construction with diagonally laid nylon plies for strength
- Strong, stiff sidewalls for stability under load



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164135702	7.00-15LT	105/101L	D/8	TL	5.5	8	30	19	2040
1164136753	7.50-16LT	116/112L	E/10	TL	6.0	9	32	22	2755

LOW PLATFORM TRAILER**Gladiator LOW BOY**

Suitable for drive & steer positions – especially effective on multi-wheel drive trucks

- High load-carrying capacity – engineered for concentrated trailer axle loads
- Straight-tracking, easy-rolling trailer tire
- Designed for low bed trailers



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164097145	7-14.5	110/105J	F/12	TL	6.0	7	27	8	2335
1164098142	8-14.5	117/112J	F/12	TL	6.0	8	28	9	2835
1164098144	8-14.5	120J	G/14	TL	6.0	8	28	9	3085

BIAS TRAILER**Gladiator QR15-STB**

Designed for towed vehicles

- Designed for trailers for optimal straight-line tracking
- Reinforced nylon plies provide a tough, and dependable performance
- Thick sidewalls resist flexing, helping trailers stay stable and controlled

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1942041831	ST175/80D13/6	91/87L	C/6	TL	5.0	7	24	8	1360
1942042041	ST205/75D14/6	100/96L	C/6	TL	5.5	8	26	9	1760
1942042051	ST205/75D15/6	101/97L	C/6	TL	5.5	8	27	9	1820
1942042252	ST225/75D15/8	113/108L	D/8	TL	5.5	9	28	9	2540

BIAS TRAILER**Gladiator HST**

Trailer tires for small and medium sized trailers

- Flatter profile for excellent handling at highway speeds
- Reinforced nylon plies provide a tough, and dependable performance.
- Thick sidewalls resist flexing, helping trailers stay stable and controlled

TREAD	PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
A	1162112481	4.80-8/6	71M	C/6	TL	3.8	5	17	5	760
A	1162118572	5.70-8/8	77M	D/8	TL	4.5	6	18	5	910
A	1162118481	4.80-12/6	80M	C/6	TL	3.8	5	21	5	990
A	1162112531	5.30-12/6	82M	C/6	TL	4.3	5	16	5	1050
B	1162118161	16.5X6.50-8/6	72M	C/6	TL	5.4	6	18	5	785
B	1162118181	18.5X8.50-8/6	78M	C/6	TL	7.0	8	20	8	935
B	1162110201	20.5X8-10/6	84M	C/6	TL	6.0	8	20	8	1100
B	1162110204	20.5X8-10/12	99M	F/12	TL	6.0	8	20	8	1710

AG R-1**Gladiator HARVEST PRO R-1**

All purpose bias tractor tire suitable for all types of soil conditions. Long bar tread for superior traction, tread-wear, and improved roadability

- Long bar design provides superior traction in the field and excellent roadability
- Long wear and durability from its braced lug design
- Tough enough for even the most demanding environments

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164188324	8.3-24	106A8	8/D	TL	7.0	8	39	35	2,095
1164189524	9.5-24	109A8	8/D	TL	8.0	9	41	35	2,270
1164181124	11.2-24	113A8	8/D	TL	10.0	11	43	40	2,540
1164181224	12.4-24	111A8	6/C	TL	11.0	12	46	44	2,400
1164181424	14.9-24	124A8	8/D	TL	13.0	15	50	44	3,520
1164181624	16.9-24	123A8	8/D	TL	15.0	17	52	48	4,080
1164181128	11.2-28	115A8	8/D	TL	10.0	11	47	40	2,680
1164181228	12.4-28	119A8	8/D	TL	11.0	12	50	44	3,000
1164181328	13.6-28	126A8	10/E	TL	12.0	14	52	44	3,740
1164181428	14.9-28	126A8	8/D	TL	13.0	15	54	44	3,740
1164181630	16.9-30	136A8	10/E	TL	15.0	17	58	48	4,940
1164181830	18.4-30	135A8	8/D	TL	16.0	18	61	48	4,800
1164181834	18.4-34	137A8	8/D	TL	16.0	18	65	48	5,080
1164181338	13.6-38	126A8	8/D	TL	12.0	14	62	44	3,740
1164181538	15.5-38	129A8	8/D	TL	14.0	16	62	40	4,080
1164181838	18.4-38	139A8	8/D	TL	16.0	18	69	48	5,360

EXPERIENCE THE DIFFERENCE®

AG R-1/G-1
Gladiator HARVEST PRO R-1


For high torque compact tractor applications to provide improve traction and ride comfort

- Deep self-cleaning lugs for excellent traction
- Suitable for multiple field conditions including soft soils
- Special tread compound resists tears and punctures

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164186014	6-14	66A6	4/B	TL	5.0	6	25	30	660
1164187014	7-14	80A6	6/C	TL	6.0	7	27	30	990
1164187016	7-16	84A6	6/C	TL	6.0	7	29	30	1,100
1164188016	8-16	91A6	6/C	TL	6.0	8	31	31	1,360

IRRIGATION
Gladiator PIVOT WORKS R1


Tubeless irrigation tire designed for durability, traction, and minimal soil impact

- Open tread center for improved cleaning
- Rounded cavity shape reduces crop and soil disturbance
- Anti-ozon compound extends the life of the tire

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1604011241	11.2-24	106A8	6	TL	W10	11	743	40	2090
1604014941	14.9-24	119A8	6	TL	W13	15	50	44	3000
1604011381	11.2-38	114A8	6	TL	W10	11	57	37	2600

IRRIGATION**Gladiator PIVOT WORKS ND**

Tubeless irrigation tire designed for durability, traction, and minimal soil impact

- Non-directional tread provides consistent traction regardless of travel direction
- Open tread for improved self-cleaning
- Anti-ozone compound extends the life of the tire

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1604031241	11.2-24	106A8	6	TL	W10	11	43	47	2090
1604034941	14.9-24	119A8	6	TL	W13	15	50	50	3000
1604031381	11.2-38	114A8	6	TL	W10	11	57	47	2600

AG R4**Gladiator INDUSTRIAL R4**

For industrial, construction, and mixed-use applications where equipment frequently transitions between hard and softer surfaces

- Lug pattern designed for smoother roading between job sites
- Large lugs for puncture and wear resistance
- Rim guard to protect wheel flange in rough service areas

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164062412	16.9-24	149A8	12	TL	15.0	17	52	34	7160
1164061724	17.5L-24	144A8	10	TL	15.0	18	49	34	6150
1164061924	19.5L-24	151A8	12	TL	17.0	19	52	35	7600
1164062112	21L-24	155A8	12	TL	18.0	21	54	36	8550
1164062816	16.9-28	148A8	10	TL	15.0	17	56	35	6930

AG I-3
Gladiator[®] TRACTION I-3


For backhoe loaders, compact loaders and compact dumpers in digging and loading applications

- Durable tread pattern for high flotation and superior stability
- Designed to resist chunking and tearing
- Wide, sturdy overlapping lugs for long wear and good traction

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164121018	10.5/80-18	135A8	12	TL	9.0	11	35	26	4800
1164121218	12.5/80-18	146/134A8	14	TL	9.0	12	38	35	6610

AG F-2M
Gladiator[®] HARVEST PRO F-2M


Steer tire for two-wheel drive tractors featuring a wide footprint for more surface contact

- Four ribs provide stability and reduced lateral slip on harder ground.
- Steers easily and offers excellent load distribution and flotation
- Excellent scuff resistance

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164049515	9.5L-15	102A8	8/D	TL	8.0	10	31	31	1,870
1164041115	11L-15	106A8	8/D	TL	8.0	11	32	31	2,090
1164041016	10.00-16	110A8	8/D	TL	8.0	11	35	23	2,340
1164041116	11.00-16	114A8	8/D	TL	10.0	12	38	25	2,600
1164041412	14L-16.1	127A8	12/F	TL	11.0	14	39	35	3,860

AG F-2**Gladiator HARVEST PRO F-2**

Ideal for two-wheel tractors operating primary in farm work where soil penetration and direction control are crucial

- High center rib digs into loose soil, offering excellent steering response
- Increased resistance toward stubble damage
- Self cleaning tread design enhanced steering performance

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164144012	4.00-12	56A8	4	TL	3.0	4	21	13	495
1164144015	4.00-15	62A8	4/B	TL	3.0	4	24	15	585
1164145015	5.00-15	69A8	4	TL	3.0	5	26	21	715
1164147515	11L-15	106A8	8/D	TL	8.0	11	32	35	2,090
1164149515	7.5L-15	93A8	6/C	TL	6.0	8	29	19	1,430
1164141115	9.5L-15	102A8	8/D	TL	7.0	9	31	28	1,870
1164175016	10.00-16	110A8	8	TL	8.0	11	35	23	2,340
1164176016	11.00-16	114A8	8	TL	10.0	12	38	36	2,600
1164176516	5.50-16	75A8	4	TL	4.0	6	28	21	855
1164171016	6.00-16	85A8	6	TL	4.0	6	29	25	1,140
1164171116	6.50-16	88A8	6	TL	4.5	7	30	27	1,230
1164177516	7.50-16	99A8	8	TL	5.5	8	32	26	1,710
1164177518	7.50-18	97A8	6	TL	5.5	8	34	25	1,510
1164174019	4.00-19	69A8	4	TL	3.0	4	28	13	715

AG F-3**Gladiator INDUSTRIAL FRONT**

Industrial front tractor tire designed primarily for hard surface applications

- Multi-rib design for improved handling and roadability
- Large footprint and deep grooves for long, even wear
- Provides superior traction on hard soil, asphalt and concrete

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164051115	11L-15	110A8	10/E	TL	8.0	11	31	16	2340
1164051116	11L-16	116A8	12/F	TL	8.0	11	32	16	2760

AG I-1
Gladiator HARVEST PRO I-1


Farm implement tire offering a wide tread for flotation, tracking and steering, and extra-wide shoulder ribs for long service life

- Wide tread for good flotation, tracking and steering
- Increased resistance toward stubble damage
- Tubeless design

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164169514	9.5L-14	111B	8/D	TL	7.0	9	29	9	2,400
1164161114	11L-14	112B	8/D	TL	8.0	11	30	9	2,470
1164169015	5.90-15	85B	4/B	TL	4.5	6	26	9	1,140
1164167015	6.70-15	97B	6/C	TL	4.5	7	28	9	1,610
1164166015	7.60-15	106B	8/D	TL	5.5	8	29	9	2,090
1164169515	9.5L-15	112B	8/D	TL	7.0	9	30	9	2,470
1164161595	9.5L-15	121B	12/F	TL	7.0	9	30	9	3,200
1164161115	11L-15	113B	8/D	TL	8.0	11	31	9	2,540
1164161215	11L-15	121B	12/F	TL	8.0	11	31	9	3,200
1164162515	12.5L-15	127B	12/F	TL	10.0	13	32	9	3,860
1164163113	31x13.50-15	120B	10/E	TL	10.0	14	31	9	3,080
1164161116	11L-16	115B	8/D	TL	8.0	11	32	9	2,680
1164162516	12.5L-16	128B	12/F	TL	10.0	13	33	9	3,960
1164161416	14L-16.1	127B	8/D	TL	11.0	14	37	13	3,860
1164161616	16.5L-16.1	138B	10/E	TL	14.0	16	40	13	5,200

AG FI
Gladiator HARVEST PRO FI


DOT approved (FI) Implement tire for intermittent use at highway speeds to help get you to and from the fields faster

- Designed for implements and wagons transported intermittently at highway speeds
- Superior load capacity over comparable I-1 tires at field speeds
- Extra-wide shoulder ribs for long service life

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164159515	9.5L-15FI	120J	10/E	TL	7.0	9	30	12	3080 @ 62mph 3695 @ 30mph
1164151115	11L-15FI	128J	12/F	TL	8.0	11	31	12	3960 @ 62mph 4752 @ 30mph
1164151215	12.5L-15FI	134J	12/F	TL	10.0	13	32	12	4680 @ 62mph 5616 @ 30mph

SKID STEER LOADER**Gladiator SKS RG**

General purpose tire offering excellent traction in light-duty applications

- Durable tread pattern for high flotation, traction, and stability
- Heavy gauge sidewall with rim guard to protect rim and reduce sidewall damage
- Designed to resist chunking and tearing

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164031016	10-16.5	134A2	E/10	TL	8.0	10	30	23	4680
1164031216	12-16.5	145A2	F/12	TL	8.0	12	33	25	6400

SKID STEER LOADER**Gladiator SKS RG HD**

Premium tire offering excellent traction in heavy duty applications including construction

- Rugged construction for reliability and fewer service interruptions
- Overlapping lugs with open shoulder for superior traction
- Heavy gauge sidewall with a wider rim guard to protect rim and reduce sidewall damage

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164012785	27X8.50-15	101B	D/8	TL	8	8	27	20	1820
1164012710	27X10.50-15	103B	D/8	TL	8	10	27	20	1930
1164011165	10-16.5	134A2	E/10	TL	8	10	30	20	4710
1164011216	12-16.5	145A2	F/12	TL	8	12	33	26	6400
1164013151	31.5X13.00-16.5	128A3	E/10	TL	9.75	13	31	30	3925
1164013315	33X15.50-16.5	137A3	F/12	TL	12	16	33	32	5050
1164011417	14-17.5	155A2	G/14	TL	8	14	36	28	8540
1164011519	15-19.5	161A2	G/14	TL	8	15	40	28	10200

SKID STEER LOADER**Gladiator[®] SKS TRAX ND**

The block pattern is ideal for hard/paved surfaces and heavy-duty service

- Higher lug-to-void ratio for better durability and wear
- Special compound for superior life on hard surfaces
- Designed to maintain broadest footprint and maximum grip
- Rim guard to reduce sidewall damage

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164021016	10-16.5	134A2	E/10	TL	8.0	10	30	47	4710
1164021216	12-16.5	145A2	F/12	TL	8.0	12	33	55	6400

SKID STEER LOADER**Gladiator[®] SKS L-4 HD**

Premium deep tread tire for severe service and heavy load applications

- Deep tread, rim guard, and extra-thick sidewall ensures long service life
- Suitable for scrap yards, mining and recycling operations
- Special compounds and heavy-duty construction minimize punctures

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164191016	10-16.5	134A2	10/E	TL	8.3	10	30	44	4800
1164191216	12-16.5	147A2	14/G	TL	9.8	12	33	44	6780

TRENCHER**Gladiator[®] TRENCHER**

For trenchers, ditching machines, and compact tractor applications

- Open lug design offers excellent traction in soft soil
- Special cut and chip resistance compound minimizes tire wear, cuts and bruises
- Multi-purpose design for both industrial and agricultural use

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164003115	31X15.5-15	121B	E/10	TL	8.0	15	31	26	3200

FORKLIFT**Gladiator POWER LIFT HD**

A premium tire for material handling equipment operating in the most demanding applications

- Deep tread with special compounds provide long even wear
- Robust casing and thick sidewall with rim guard for excellent durability
- Wide, flat tread profile provides excellent stability in forklift applications

PRODUCT ID	SIZE	LR	SPEED (MPH)	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	POSITION	MAX LOAD (S/LBS)
1164205080	5.00-8	8/D	15	TT+FLAP	3.0	5	18	17	Load Wheel	1820
									Steer Wheel	-
1164206090	6.00-9	10/E	15	TT+FLAP	4.0	6	21	20	Load Wheel	3300
									Steer Wheel	2830
1164206510	6.50-10	12/F	15	TT+FLAP	5.0	7	24	20	Load Wheel	4300
									Steer Wheel	3640
1164207012	7.00-12	16/H	15	TT+FLAP	5.0	8	25	20	Load Wheel	6240
									Steer Wheel	5110
1164207015	7.00-15 (30X8-15)	16/H	15	TT+FLAP	6.0	8	30	16	Load Wheel	6010
									Steer Wheel	-
1164207515	7.50-15	14/G	15	TT+FLAP	6.0	8	32	20	Load Wheel	8050
									Steer Wheel	6150
1164208115	8.15-15 (28X9-15)	14/G	15	TT+FLAP	7.0	9	28	17	Load Wheel	6800
									Steer Wheel	5680
1164208215	8.25-15	14/G	15	TT+FLAP	6.5	9	33	20	Load Wheel	8550
									Steer Wheel	7150

* TT + FLAP = TUBETYPE TIRE WITH FLAP

EXPERIENCE THE DIFFERENCE®

OFF-THE-ROAD G-2**Gladiator GRADER G-2**

For road graders and telescopic handlers operating in both soft muddy soil and heavy dirt

- Provides consistent grip on soil, gravel, and hard-packed surfaces, improving grading performance
- Heavyweight tire for superior durability and performance
- Special cut and chip resistance compound minimizes tire wear, cuts and bruises

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164211324	14.00-24	143A8	12/F	TL	8.00TG	13	50	30	6000
1164211424	13.00-24	147A8	12/F	TL	8.00TG	14	53	34	6800

OFF-THE-ROAD L-2**Gladiator LOADER L-2**

Ideal for wheel loaders in construction, landscaping, and agriculture applications

- Excellent grip on soft ground, improving machine performance
- Multi-purpose design for maximum traction, slippage resistance and superior wear
- Deep, flat tread and durable compounds promote even wear, extending service life

PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164221525	15.5-25	168A2	12/F	TL	12.0	16	50	30	12300
1164221725	17.5-25	171A2	12/F	TL	14.0	18	53	30	13600
1164221625	17.5-25	177A2	16/H	TL	14.0	18	53	30	16100
1164222025	20.5-25	174A2	12/F	TL	17.0	21	59	35	14800
1164222520	20.5-25	181A2	16/H	TL	17.0	21	59	35	18200

SPECIALTY AG/TRENCHER
Gladiator AG TRAC

Designed for Compact Tractors and Mini Trenchers for maximum performance

- Overlapping center lugs for a smooth ride
- Long-bar tread design for traction and stability
- Heavy duty sidewall to improve puncture resistance



PRODUCT ID	SIZE	LOAD INDEX	LR	TYPE	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164231305	13X5.00-6	52A4	4/B	TL	3.5	4.8	12.6	10	440
1164238008	4.80/4.00-8	43A6	4/B	TL	3.0	4	17	22	340
1164231665	16X6.50-8	64A4	4/B	TL	5.38	6.5	16.0	12	620
1164232312	23X10.50-12	90A4	4/B	TL	8.5	10.4	22.6	18	1320
1164232612	26X12.00-12	100A4	4/B	TL	10.5	12	26	25	1760
1164232608	26X12.00-12	119A4	8/D	TL	10.5	12.1	25.5	25	3000

GOLF CART
Gladiator PRO

- Sawtooth tread design minimizes compaction, preserving grass quality
- Designed for golf courses and park grass environments



PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32nds)	MAX LOAD (S/LBS)
1401010317	18X8.50-8	B/4	7.0	8	18	7	825

GOLF CART
Gladiator P4C

- Turf-friendly design offers optimized weight disbursement for reduced turf disturbance
- Wide footprint offers maximum traction and promotes longer tread life



PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401010317	18X8.50-8	B/4	7.0	8	18	7	825

GOLF CART**Gladiator PGC**

- Low profile design for a custom, high-end look
- Wide footprint for excellent traction on both turf and paved surfaces
- High J Speed rating

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401039401	205/50-10	B/4	6.5	8	18	11	825

LAWN AND GARDEN**Gladiator TURF**

Designed for Compact Tractors and Mini Trenchers for maximum performance

- Overlapping center lugs for a smooth ride
- Long-bar tread design for traction and stability
- Heavy duty sidewall to improve puncture resistance

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401041143	4.10/3.50-4	B/4	3.3	4	11	4	340
1401041144	11X4.00-4	B/4	3.3	3	11	4	340
1401041145	11X4.00-5	B/4	3.0	4	11	4	330
1401049734	13X5.00-6	B/4	3.5	5	13	4	440
1401049708	13X6.50-6	B/4	5.0	6	13	4	480
1401049758	15X6.00-6	B/4	4.5	6	14	6	565
1401041118	4.80/4.00-8	B/4	3.8	5	17	4	660
1401046867	16X6.50-8	B/4	5.4	6	16	9	615
1401044495	16X7.50-8	B/4	5.4	7	16	8	680
1401042185	18X6.50-8	B/4	5.0	6	18	9	760
1401049401	18X7.00-8	B/4	5.4	7	18	9	785
1401040317	18X8.50-8	B/4	7.0	8	18	9	825
1401043333	18X9.50-8	B/4	7.0	9	18	9	935
1401047971	20X10.00-8	B/4	8.0	10	20	9	1,200
1401042857	18X8.50-10	B/4	7.0	8	19	10	805
1401045556	20X8.00-10	B/4	6.0	8	19	9	910
1401040541	18X10.50-10	B/4	8.5	10	19	10	990
1401045652	20X10.00-10	B/4	8.0	10	20	10	1,170
1401043785	23X8.50-12	B/4	7.0	8	23	10	1,100
1401049614	23X9.50-12	B/4	7.0	9	23	10	1,230
1401049565	23X10.50-12	B/4	8.5	10	23	10	1,320
1401046746	24X9.50-12	B/4	7.0	9	24	9	1,520
1401042999	24X12.00-12	B/4	9.5	12	24	9	1,710
1401045942	26X12.00-12	B/4	10.5	12	26	12	1,760

LAWN AND GARDEN**Gladiator S-TURF**

- Wide footprint provides a nice smooth ride and high flotation for minimal compaction
- Turf-friendly tread with siped lugs for excellent traction

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401116522	22.5X10.00-8	B/4	7.0	10	23	12	1320
1401115652	22X9.50-10	B/4	7.0	10	23	12	1230
1401110234	24X12.00-10	B/4	7.8	11	25	12	1710

LAWN AND GARDEN**Gladiator STRAIGHT RIB**

- Straight rib design for minimal turf damage
- Square shoulder design for maximum traction and weight distribution
- Suitable for golf, mowers and other applications

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401060119	11X4.00-5	B/4	3.0	3	11	3	330
1401069734	13X5.00-6	C/6	3.5	4	13	4	505
1401069708	13X6.50-6	C/6	5.0	5	13	4	583
1401069758	15X6.00-6	C/6	4.5	5	14	4	715
1401066867	16X6.50-8	C/6	5.4	5	16	5	740
1401061862	18X8.50-8	B/4	7.0	7	18	5	825
1401068115	18X9.50-8	B/4	7.0	7	18	5	935

LAWN AND GARDEN**Gladiator TURF TRAC**

- Turf-friendly chevron tread provides excellent traction
- Easy cleaning tread design

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401076522	20x8.00-8	A/2	6.5	8	20	6	600
1401072999	24x12.00-12	B/4	9.5	12	24	8	1,710

LAWN AND GARDEN**Gladiator SMOOTH**

- Smooth design for minimized turf damage
- Square shoulder design for maximum traction and weight distribution

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401050119	11X4.00-5	B/4	3.0	4	11	N/A	330
1401059734	13X5.00-6	B/4	3.5	5	13	N/A	440
1401059708	13X6.50-6	B/4	5.0	6	13	N/A	480
1401058115	18X9.50-8	B/4	7.0	9	18	N/A	935

LAWN AND GARDEN**Gladiator SAWTOOTH**

- Wide footprint provides a nice smooth ride and high flotation for minimal compaction
- Turf-friendly tread with siped lugs for excellent traction

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401088739	2.80/2.50-4	B/4	2.3	3	9	3	300
1401080119	4.10/3.50-4	B/4	3.3	4	11	4	340
1401089903	4.10/3.50-5	B/4	3.3	4	12	4	380
1401085675	4.10/3.50-6	B/4	3.3	4	13	4	430
1401086038	5.30/4.50-6	B/4	4.3	5	15	4	615

LAWN AND GARDEN**Gladiator *STUD***

- Stud design for long-wearing traction
- Used on hand trucks, small garden trailers and yard carts

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401090119	4.10/3.50-4	B/4	3.3	4	11	5	340
1401099903	4.10/3.50-5	B/4	3.3	4	12	5	380
1401095675	4.10/3.50-6	B/4	3.3	4	13	5	430
1401097412	4.80/4.00-8	B/4	3.8	5	17	7	660

LAWN AND GARDEN**Gladiator *WHEELBARROW***

- Wheelbarrow rib design for smooth, easy control
- Round shoulder design for less rolling resistance

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401104578	4.8/4.00-6	A/2	2.5	4	13	3	390
1401101118	4.8/4.00-8	B/4	3.8	5	17	3	660

ATV**Gladiator[®] KNOBBY**

- Staggered knobby design for exceptional traction on hard surfaces
- Designed for soft and hard surfaces

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401120879	AT145/70-6	1*/2PR	5.5	6	14	6	165
1401128115	18X9.50-8	A/2	7.0	9	18	11	225
1401122135	AT20X7-8	2*/4PR	5.5	7	20	10	195
1401123232	AT22X11-8	2*/4PR	9.0	11	22	13	340
1401129565	AT25X12-9	2*/4PR	9.5	12	25	13	430
1401125701	AT22X11-10	2*/4PR	9.0	11	22	18	330

ATV**Gladiator[®] MUD & SAND**

- Heavy center bar for maximum traction and cleanout
- Knobby design in shoulder area for added traction

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401137143	AT25X13-9	3*/6PR	10.5	13	25	21	535

ATV**Gladiator[®] TRAIL HD**

- Large knobs provide maximum traction and cleanout
- Tread provides exceptional tread life

PRODUCT ID	SIZE	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401137143	AT22X11-10	3*/6PR	9.0	11	22	19	385

ATV / SXS**Gladiator R/T UTV**

- Tread design for deep down traction, even in the muddiest conditions
- Reinforced knobs to reduce knob rollover at low pressure, improve ride comfort and increase tread life

PRODUCT ID	SIZE	LI	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1401150085	AT25X11-10	53F	3*/6PR	9.0	11	25	32	455
1401159622	AT25X8-12	43F	3*/6PR	6.5	8	25	32	340
1401158421	AT25X10-12	50F	3*/6PR	8.0	10	25	32	420
1401150987	AT26X9-12	49F	3*/6PR	7.0	9	26	32	410
1401158889	AT26X12-12	58F	3*/6PR	9.5	12	26	32	520
1401159903	AT27X9-12	52F	3*/6PR	7.0	9	27	32	440
1401153729	AT27X12-12	60F	3*/6PR	9.5	12	27	32	550

Gladiator® Tires

EXPERIENCE THE DIFFERENCE®

ATV / SXS**Gladiator XTR UTV RADIAL**

- Radial construction provides smooth ride over rough terrain
- 8 ply construction for improved and durability
- Wrap around lugs provide improved shoulder protection

PRODUCT ID	SIZE	LI	LR	RIM	SW (IN)	OD (IN)	TD (32NDS)	MAX LOAD (S/LBS)
1164242512	25X8.00R12	68L	8/D	7	8	25	26	696
1164241012	25X10.00R12	75L	8/D	8	10	25	26	855
1164241112	25X11.00R12	77L	8/D	9	11	25	26	910
1164249012	26X9.00R12	74L	8/D	7	9	26	26	828
1164242612	26X11.00R12	80L	8/D	9	11	26	26	996
1164242614	26X9.00R14	73L	8/D	7	9	26	26	801
1164242614	26X11.00R14	79L	8/D	9	11	26	26	966
1164242794	27X9.00R14	75L	8/D	7	9	27	26	849
1164242714	27X11.00R14	82L	8/D	9	11	27	26	1041
1164242814	28X10.00R14	80L	8/D	8	10	28	26	1002
1164243014	30X10.00R14	85L	8/D	8	10	30	26	1134
1164243214	32X10.00R14	89L	8/D	8	10	32	26	1293
1164243415	34X10.00R15	91L	8/D	8	10	34	35	1350

GLADIATOR BIAS HIGHWAY TIRE LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new Gladiator Bias Highway (DOT approved) Tire purchased on or after April 1, 2026 from API bearing the brand name Gladiator to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32". The life of the original usable tread ends when the tire tread has worn to 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Gladiator Bias Highway tire becomes unserviceable due to material or workmanship, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Gladiator tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit excluding FET will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining as measured in the fastest wearing groove. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is applicable only in the United States, and Canada and any tire used or equipped on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 2. Tires that are deemed out-of-round or out-of-balance
 3. Failure, damage or irregular wear due to:
 - a. Road hazards
(i.e. puncture, cut, snag, impact breaks, etc. except as authorized in the Field Hazard and Stubble Damage Limited Warranty), collision;
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including but not limited to improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another and;
 4. Cost of service, mounting and dismounting.
 5. Loss of time or use, inconvenience, or any incidental or consequential damages
 6. Tires older than five (5) years from date of manufacture as determined by the tire serial number.
 7. Tires deemed to be out of round or out of balance.

OWNERS OBLIGATIONS

In order to be eligible for API Limited Warranty Service, the owner must:

- A. Present the tire to an authorized API dealer.
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer; and,
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

GLADIATOR OFF HIGHWAY TIRE LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new Gladiator Off Highway Tire (including Farm FI) purchased on or after April 1, 2026 from API bearing the brand name Gladiator to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32". The life of the original usable tread ends when the tire tread has worn to 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If a Gladiator tire becomes unserviceable due to workmanship or materials within the first 10% of tread life, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Gladiator tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit excluding FET will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining as measured in the fastest wearing groove. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

FIELD HAZARD AND STUBBLE DAMAGE LIMITED WARRANTY

If in normal agricultural service, any Gladiator Agricultural (Farm- R-1, Irrigation, R-4, F-2M, F-2, I-3, I-1, and FI) tire that becomes unserviceable as the result of field hazard or stubble damage, it is covered by this Field Hazard and Stubble Damage Warranty. This limited warranty provides an adjustment credit only. The adjustment credit below is applicable to the purchase price of a new comparable Gladiator or equivalent replacement tire. You must also pay the cost of mounting the replacement tire, applicable taxes, and any other services you may require.

DATE OF PURCHASE	ORIGINAL TREAD DEPTH USED	ADJUSTMENT CREDIT
Less than 12 Months	Less than 25%	50%
Up to 24 Months	Less than 50%	25%

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is applicable only in the United States, and Canada and any tire used or equipped on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 2. Tires that are deemed out-of-round or out-of-balance
 3. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc. except as authorized in the Field Hazard and Stubble Damage Limited Warranty), collision;
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including but not limited to improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another and;
 4. Cost of service, mounting and dismounting.
 5. Loss of time or use, inconvenience, or any incidental or consequential damages
 6. Tires older than five (5) years from date of manufacture as determined by the tire serial number.
 7. Tires deemed to be out of round or out of balance.

OWNERS OBLIGATIONS

In order to be eligible for API Limited Warranty Service, the owner must:

- A. Present the tire to an authorized API dealer.
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer; and,
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

Gladiator[®] **Tires**



GLADIATORTIRES.COM



800.944.8414

GLADIATOR ON AND OFF HIGHWAY TIRES - AUGUST 2026
